

SUSE Linux Enterprise Server

10 SP4

www.novell.com

April 15, 2011

Start-Up Guide



Start-Up Guide

All content is copyright © Novell, Inc.

Legal Notice

This manual is protected under Novell intellectual property rights. By reproducing, duplicating or distributing this manual you explicitly agree to conform to the terms and conditions of this license agreement.

This manual may be freely reproduced, duplicated and distributed either as such or as part of a bundled package in electronic and/or printed format, provided however that the following conditions are fulfilled:

That this copyright notice and the names of authors and contributors appear clearly and distinctively on all reproduced, duplicated and distributed copies. That this manual, specifically for the printed format, is reproduced and/or distributed for noncommercial use only. The express authorization of Novell, Inc must be obtained prior to any other use of any manual or part thereof.

For Novell trademarks, see the Novell Trademark and Service Mark list <http://www.novell.com/company/legal/trademarks/tmlist.html>. * Linux is a registered trademark of Linus Torvalds. All other third party trademarks are the property of their respective owners. A trademark symbol (®, ™ etc.) denotes a Novell trademark; an asterisk (*) denotes a third party trademark.

All information found in this book has been compiled with utmost attention to detail. However, this does not guarantee complete accuracy. Neither Novell, Inc., SUSE LINUX Products GmbH, the authors, nor the translators shall be held liable for possible errors or the consequences thereof.

Contents

Preface	v
Part I Installation on x86, AMD64, Intel 64, and Itanium Processor Family	1
1 Installation Considerations	3
1.1 Installation Type	3
1.2 Boot Methods	3
1.3 Installation Source	4
1.4 Installation Target	5
1.5 Different Installation Methods	5
2 Installation Procedure	7
2.1 Booting from a Local Interchangeable Drive	7
2.2 Installing over the Network	8
2.3 Controlling Installation Remotely	8
Part II Installation on IBM POWER	9
3 Installation Considerations	11
3.1 Types of Installation	11
3.2 IPL Options	12
3.3 Installation Source	12
3.4 Installation Targets	13
3.5 Connecting to the Installation System	14

4	Installation Procedure	15
4.1	Installing in an Entire System	15
4.2	Installing in an LPAR	16
Part III Installation on IBM System z		19
5	Installation Considerations	21
5.1	Types of Installation	21
5.2	IPL Options	22
5.3	Installation Source	22
5.4	Initiating a Connection to the Installation System	23
6	Installation Procedure	25
6.1	LPAR Installation	25
6.2	z/VM Installation	26

Preface

This short manual offers a quick introduction to the installation of your SUSE Linux Enterprise Server. It features an overview of the various fields of application and installation types of each of the platforms supported by SUSE Linux Enterprise Server as well as a short description of the installation procedure.

Quality service is also available. Experts can answer questions about installation or configuration, make reliable security updates available, and support development projects.

1 Feedback

We want to hear your comments and suggestions about this manual and the other documentation included with this product. Please use the User Comments feature at the bottom of each page of the online documentation and enter your comments there.

2 Additional Documentation

For additional documentation on this product, refer to <http://www.novell.com/documentation/sles10/index.html>:

Architecture-Specific Information

Architecture-specific information needed to prepare a SUSE Linux Enterprise Server target for installation.

Installation and Administration

In-depth installation and administration for SUSE Linux Enterprise Server.

For a documentation overview on the SUSE® Linux Enterprise Desktop product, refer to <http://www.novell.com/documentation/sled10/index.html>.

3 Documentation Conventions

The following typographical conventions are used in this manual:

- `/etc/passwd`: filenames and directory names
- *placeholder*: replace *placeholder* with the actual value
- `PATH`: the environment variable `PATH`
- `ls, --help`: commands, options, and parameters
- `user`: users or groups
- `Alt, Alt + F1`: a key to press or a key combination; keys are shown in uppercase as on a keyboard
- *File, File > Save As*: menu items, buttons
- ▶ **amd64 ipf**: This paragraph is only relevant for the specified architectures. The arrows mark the beginning and the end of the text block. ◀
 - ▶ **ipseries s390 zseries**: This paragraph is only relevant for the specified architectures. The arrows mark the beginning and the end of the text block. ◀
- *Dancing Penguins* (Chapter *Penguins*, ↑Another Manual): This is a reference to a chapter in another manual.

**Part I. Installation on x86,
AMD64, Intel 64, and Itanium
Processor Family**

Installation Considerations

This chapter encompasses all the decisions that need to be made before installing SUSE® Linux Enterprise Server on x86, AMD64, Intel 64, and Itanium hardware. Find the current hardware and software requirements for installing SUSE Linux Enterprise Server on x86, AMD64, Intel 64, and Itanium in the *Architecture-Specific Information* manual, which is contained on the first CD or DVD as a printable PDF in the `/docu` directory.

1.1 Installation Type

SUSE Linux Enterprise Server is normally installed as an independent operating system. With the introduction of Xen, it is also possible to run multiple instances of SUSE Linux Enterprise Server on the same hardware. However, the controlling Domain-0 installation for Xen is done like a typical installation with some additional packages. The installation of Xen guests is described in *Installation and Administration*, which is available in the installed system as well as on the first CD or DVD.

1.2 Boot Methods

Depending on the hardware used, the following boot methods are available for the first boot procedure prior to the installation of SUSE Linux Enterprise Server:

Table 1.1 *Boot Options*

Boot Option	Use
CD or DVD drive	The simplest booting method. The system requires a locally-available CD-ROM or DVD-ROM drive for this.
Floppy or USB disks	Find the images required for creating boot disks on the first CD or DVD in the <code>/boot</code> directory. See also the <code>README</code> in the same directory. Booting from a USB memory stick is only possible if the BIOS of the machine supports booting from it.
PXE or bootp	Must be supported by the BIOS or by the firmware of the system used. This option requires a boot server in the network. This task can be handled by another SUSE Linux Enterprise Server.
Hard disk	SUSE Linux Enterprise Server can also be booted from hard disk. For this, copy the kernel (<code>linux</code>) and the installation system (<code>initrd</code>) from the <code>/boot/loader</code> directory of the first CD or DVD onto the hard disk and add an appropriate entry to the boot loader.

1.3 Installation Source

When installing SUSE Linux Enterprise Server, the actual installation data must be available in the network, on a hard disk partition, or on a local CD-ROM or DVD. To install from the network, you need an installation sever. To make the installation data available, set up any computer in a Unix or Linux environment as an NFS, HTTP, or FTP server. To make the installation data available from a Windows computer, release the data with SMB.

The installation source is particularly easy to select if you configure an *SLP server* in the local network. For more information, see Section “Setting Up the Server Holding the Installation Sources” (Chapter 4, *Remote Installation, ↑ Installation and Administration*).

1.4 Installation Target

Most installations are to a local hard disk. Therefore, it is necessary for the hard disk controllers to be available to the installation system. If a special controller, like a RAID controller, needs an extra kernel module, provide a kernel module update disk to the installation system.

Other installation targets may be all kinds of block devices that provide sufficient disk space and speed to run an operating system. This includes network block devices like iSCSI or SAN. It is also possible to install on network file systems that offer the standard Unix permissions. However, it may be problematic to boot these, because they must be supported by the `initramfs` before the actual system can start. Such installations are useful if there is a need to start the same system in different locations or if you intend to use Xen features like domain migration.

1.5 Different Installation Methods

SUSE Linux Enterprise Server offers several different methods for controlling installation:

- Installation on the console
- Installation via serial console
- Installation with AutoYaST
- Installation via SSH
- Installation with VNC

By default, the console is used. If you have a large number of similar computers to install, it is advisable to create an AutoYaST configuration file and make this available to the installation process. See also the documentation for `autoyast2` in Chapter 5, *Automated Installation* (↑*Installation and Administration*).

Installation Procedure

This chapter offers an overview of the steps required for the complete installation of SUSE® Linux Enterprise Server in the required mode. Find detailed information about the preparations for installing SUSE Linux Enterprise Server on x86, AMD64, Intel 64, and Itanium in the *Architecture-Specific Information* manual, which is available as a printable PDF in the `/docu` directory on the first CD or DVD. *Reference* contains a full description of how to install and configure the system with YaST.

2.1 Booting from a Local Interchangeable Drive

CD-ROM and floppy drives and USB memory sticks can be used for installation purposes. Adjust your computer to your needs:

1. Make sure that the drive is entered as a bootable drive in the BIOS.
2. Insert the boot medium in the drive and start the boot procedure.
3. The boot menu of the CD, DVD, floppy, or USB disk allows transferring different parameters to the installation system. See also Section “Using Custom Boot Options” (Chapter 4, *Remote Installation*, ↑ *Installation and Administration*). If the installation should be performed over the network, specify the installation source here.
4. If unexpected problems arise during installation, use safe settings to boot.

2.2 Installing over the Network

An installation server is required to perform the installation by using a network source. The procedure for installing this server is outlined in Section “Setting Up the Server Holding the Installation Sources” (Chapter 4, *Remote Installation*, ↑*Installation and Administration*).

If you have an SLP server, select SLP as the installation source in the first boot screen. During the boot procedure, select which of the available installation sources to use.

If the CDs or DVDs are available in the network, use these as an installation source. In this case, specify the parameter `install=<URL>` with suitable values at the boot prompt. Find a more detailed description of this parameter in Section “Using Custom Boot Options” (Chapter 4, *Remote Installation*, ↑*Installation and Administration*).

2.3 Controlling Installation Remotely

There are three options for controlling installations from a remote computer: installation via SSH, installation over serial console, and installation via VNC. These possibilities are described in the *Architecture-Specific Information* manual. Find this manual on the first CD or DVD as a printable PDF in the `/docu` directory.

Part II. Installation on IBM POWER

Installation Considerations

This chapter summarizes all decisions to make before starting an installation of SUSE® Linux Enterprise Server on IBM POWER hardware. The current hardware and software requirements for installing SUSE Linux Enterprise Server on IBM POWER devices are listed in the Chapter 1, *Requirements (↑Architecture-Specific Information)*, provided as a printable PDF document in the directory `/docu` on the first CD.

3.1 Types of Installation

SUSE Linux Enterprise Server offers two different types of installation on IBM POWER: an installation on the entire system and an installation in a logical partition (LPAR).

iSeries

Linux can only be installed in an LPAR on this type of machine. The installation on iSeries requires a telnet connection that allows control over the installation process throughout its course. An installation server in the network qualifies as a good source of installation.

pSeries

Linux can be installed on the entire system here. On IBM pSeries p630, p655, p670, and p690, it is also possible to install Linux in an LPAR. You can also start these two systems without partitioning and install on the entire system (full system partition). A CD-ROM drive, DVD drive, or an installation server in the network can be used as the installation source.

eServer i5/p5, System i5/p5, OpenPower

Linux can be installed on the entire system (unmanaged mode) or on an LPAR. A CD-ROM drive, DVD drive, or an installation server in the network can be used as the installation source.

JS20 Blade, JS21 Blade

Linux can only be installed on the entire system—on a blade—on this type of machine. A CD-ROM drive, DVD drive, or an installation server in the network can be used as the installation source.

IntelliStation, ATX Workstation and Server

Linux can only be installed on the entire system. A CD-ROM drive, DVD drive, or an installation server in the network can be used as the installation source.

3.2 IPL Options

Depending on the hardware used and on the chosen type of installation, the following options for the initial IPL are available for installing SUSE Linux Enterprise Server:

Table 3.1 *IPL Options*

IPL Option	Use
CD or DVD drive	Simplest booting procedure. The system requires a locally available CD-ROM or DVD drive for this.
Network	SUSE Linux Enterprise Server can also be booted from the network. This requires copying the appropriate kernel (<code>suseboot/inst64</code> or <code>ISERIES64</code>) from the first CD to a boot server. Booting from network can be selected in the firmware or with <code>i5/OS</code> .

3.3 Installation Source

For installing SUSE Linux Enterprise Server, the installation files must be available in the local network or on a locally provided CD-ROM or DVD. Provide a network source

by setting up a Linux or Unix system as an HTTP, NFS, or FTP server. It is also possible to share the installation files over SMB from a computer running Windows.

Configuring an *SLP server* in the local network simplifies selection of an installation source. This is described in Section “Setting Up an Installation Server Using YaST” (Chapter 4, *Remote Installation*, ↑*Installation and Administration*).

3.4 Installation Targets

SUSE Linux Enterprise Server can be installed on different types of mass storage media on IBM Power.

iSeries

- DASD (hard disk)
- IBM iSeries virtual disk

pSeries

- DASD (hard disk)
- SAN over Fiber Channel

eServer i5/p5, System i5/p5, OpenPower

- DASD (hard disk)
- Virtual SCSI
- SAN over Fiber Channel

JS20 Blade, JS21 Blade

- Local hard disk

IntelliStation, ATX Workstation and Server

- Local hard disk

3.5 Connecting to the Installation System

SUSE Linux Enterprise Server offers a selection of four different ways of connecting to the installation system: SSH, VNC, serial console, and screen console. The versions of the SSH, VNC, or terminal software vary depending on the operating system running on the workstation initiating the connection to the installation system.

It is advisable to create an AutoYaST configuration file if many identical partitions or machines need to be installed. It can then drive the installation process. Refer to the documentation for AutoYaST in Section “Rule-Based Autoinstallation” (Chapter 5, *Automated Installation*, ↑*Installation and Administration*).

Installation Procedure

This chapter provides an overview of the steps required to install SUSE® Linux Enterprise Server in the chosen mode. Detailed information about preparing an installation of SUSE Linux Enterprise Server on IBM POWER can be found in the manual *Architecture-Specific Information*, which is provided as a printable PDF document in the directory `/docu` on the first CD. A thorough description of the installation and configuration with YaST is provided in Chapter 3, *Installation with YaST* (↑*Installation and Administration*) and Chapter 8, *System Configuration with YaST* (↑*Installation and Administration*).

4.1 Installing in an Entire System

The following steps should be completed when installing in an entire system. Single blades in a blade center also count as a entire systems in this context.

- 1 Verify the hardware requirements (see also Section “Hardware Requirements” (Chapter 1, *Requirements*, ↑*Architecture-Specific Information*)).
- 2 Verify the software requirements (see also Section “Software Requirements” (Chapter 1, *Requirements*, ↑*Architecture-Specific Information*)).
- 3 Set up the system properly to enable booting from CD-ROM, DVD, or the network.
 - For pSeries, see also Section “Preparing for Installation on an IBM pSeries Models” (Chapter 2, *Preparation*, ↑*Architecture-Specific Information*). This also applies for ATX workstation and ATX server (only for the installation on an entire system).

- For eServer i5/p5, System i5/p5, and OpenPower, see also Section “Preparing for Installation on IBM eServer i5/p5, System i5/p5, and OpenPower Models” (Chapter 2, *Preparation*, ↑*Architecture-Specific Information*).
 - For JS20/JS21/JS22 Blades, see also Section “Preparing an Installation on IBM POWER JS20/JS21/JS22 Blades” (Chapter 2, *Preparation*, ↑*Architecture-Specific Information*).
- 4 Start the installation from CD-ROM, DVD, or the network. See also Section “Setting Up the Installation Source” (Chapter 2, *Preparation*, ↑*Architecture-Specific Information*).
 - 5 Install the software and perform the basic network configuration. See also Chapter 3, *Installation with YaST* (↑*Installation and Administration*).

4.2 Installing in an LPAR

- 1 Verify the hardware requirements. See also Section “Hardware Requirements” (Chapter 1, *Requirements*, ↑*Architecture-Specific Information*).
- 2 Verify the software requirements. See also Section “Software Requirements” (Chapter 1, *Requirements*, ↑*Architecture-Specific Information*).
- 3 Prepare a VNC client for the installation process. See also Section “Simple Remote Installation via VNC—Static Network Configuration” (Chapter 4, *Remote Installation*, ↑*Installation and Administration*).
- 4 Prepare the system in its firmware or on the i5/OS side:
 - For iSeries, see also Section “Preparing an Installation on IBM iSeries Models” (Chapter 2, *Preparation*, ↑*Architecture-Specific Information*)
 - For pSeries p630, p655, p670, and p690, see also Section “Preparing for Installation on an IBM pSeries Models” (Chapter 2, *Preparation*, ↑*Architecture-Specific Information*)
 - For eServer i5/p5, System i5/p5, and OpenPower, see also Section “Preparing for Installation on IBM eServer i5/p5, System i5/p5, and OpenPower Models” (Chapter 2, *Preparation*, ↑*Architecture-Specific Information*)

- 5** Configure a client for accessing the system during the installation. See also Section “Client for the Operation of the Installation Software” (Chapter 2, *Preparation*, ↑*Architecture-Specific Information*).
- 6** For iSeries, set up the IPL source on the i5/OS side and see also Section “IPL: Starting the NWSD (WRKCFGSTS *NWS)” (Chapter 2, *Preparation*, ↑*Architecture-Specific Information*).
- 7** Install the software and perform the basic network configuration. See also Chapter 3, *Installation with YaST* (↑*Installation and Administration*).

Part III. Installation on IBM System z

Installation Considerations

This chapter summarizes all decisions that must be made while planning an installation of SUSE® Linux Enterprise Server on IBM System z hardware. The current hardware and software requirements for installing SUSE Linux Enterprise Server on IBM System z are listed in the manual *Architecture-Specific Information*, which is provided as a printable PDF file in the directory `/docu` on the first installation medium.

5.1 Types of Installation

SUSE Linux Enterprise Server allows two different types of installation on IBM System z:

LPAR Installation

Installing SUSE Linux Enterprise Server for IBM System z on a separate logical partition (LPAR) allows SUSE Linux Enterprise Server to use a specific portion of the physical memory. It is furthermore possible to specify how many processors should be used. This mode allows concurrently running multiple operating systems on a system.

Installation in z/VM

z/VM mode runs SUSE Linux Enterprise Server for IBM System z as a hosted system in z/VM (*virtual machine*). This type has the advantage that z/VM provides full control over SUSE Linux Enterprise Server. This type of installation can prove very helpful for kernel development or kernel-based debugging. It is furthermore very easy to modify the hardware configuration of a hosted Linux system. The

creation of hosted SUSE Linux Enterprise Server systems is also very easy, because it is possible to run several hundred Linux instances concurrently.

Installation from an FCP-Attached DVD-ROM

An FCP-attached DVD-ROM can be used to IPL in an LPAR or in VM mode. The installation data is read directly from the DVD-ROM.

5.2 IPL Options

Depending on the hardware used and the selected type of installation, the following IPL options are available for the initial IPL prior to the installation of SUSE Linux Enterprise Server:

Table 5.1 *IPL Options*

IPL Option	Scope
ESCON/FICON attached tape	Can be used in any type of installation. The sole requirement is the availability of a tape library unit.
VM Reader	Can be used in VM mode. The necessary data must have previously been transferred into the z/VM system (for example, with FTP).
CD-ROM or Server	Can be used to IPL in an LPAR. The installation data can be read directly from DVD-ROM or loaded into the installation system with FTP.

5.3 Installation Source

In case of the FCP-attached DVD-ROM, the installation data is read from the DVD-ROM. For all other IPL options, the installation data must be available on the internal network. In a Unix or Linux environment, the installation data can be provided on a workstation set up as an NFS or FTP server. To make the installation data available from a Windows workstation, release it on an SMB share. Several FTP software packages

for Windows are available as an alternative, however, their use is not always free of problems.

5.4 Initiating a Connection to the Installation System

SUSE Linux Enterprise Server offers three different methods initiating a connection to the installation system. Select SSH, X, or VNC. Depending on the operating system running on the workstation that initiates the connection to the installation system, the versions of these applications differ.

Installation Procedure

This chapter presents an overview of the various steps necessary for a complete installation of SUSE® Linux Enterprise Server in the desired mode. Detailed information about preparing an installation of SUSE Linux Enterprise Server on IBM System z is provided in the manual *Architecture-Specific Information*, which is provided as a printable PDF file in the directory `/docu` on the first installation medium. A detailed description of the installation and configuration of the system with YaST can be found in *Reference*.

6.1 LPAR Installation

- 1 Choose a suitable IPL option for the initial IPL before installing. In the case of an LPAR installation, choose between *CD-ROM or Server* or *Tape*.
- 2 Make the installation media or their data available in the network using FTP or SMB and ensure that the paths can be accessed by YaST.
- 3 Choose one of the following:
 - Using the HMC, prepare the IPL from DVD-ROM or from the server.
 - Transfer the tape IPL kernel, the parmfile, and the initial RAM disk using FTP to the tape and make the tape drive available via IOCDS.
- 4 Perform the IPL for the installation system.

- 5 Configure the network.
- 6 Choose a type of connection to the installation system (SSH, X, or VNC) and establish the connection.
- 7 Start the basic installation with YaST.
- 8 Perform the first IPL of the installed system.
- 9 Reconnect to the installation system and start YaST to continue the installation process and configure SUSE Linux Enterprise Server.

6.2 z/VM Installation

- 1 Choose a suitable IPL option for the initial IPL before installing. For the installation in z/VM, choose *VM Reader* or *Tape*.
- 2 Make the installation media or their data available in the network using FTP or SMB and ensure that the paths can be accessed by YaST.
- 3 Create a Linux guest in z/VM, assigning its memory allowance and defining the desired network connection.
- 4 Choose one of the following:
 - Transfer the VM reader kernel, the parmfile, and the initial RAM disk using FTP to a minidisk accessible to the guest in z/VM and create a REXX start-up script for the IPL of the VM reader.
 - Transfer the tape IPL kernel, the parmfile, and the initial RAM disk using FTP to a minidisk accessible to the guest in z/VM and transfer these files to the tape using, for example, a REXX script.
- 5 Perform the IPL of the installation system.
- 6 Configure the network.

- 7** Choose the type of connection to the installation system (SSH or VNC) and establish the connection.
- 8** Start the basic installation with YaST.
- 9** Perform the first IPL of the installed system.
- 10** Reconnect to the installation system and start YaST to continue the installation process and configure the SUSE Linux Enterprise Server.

